

Bye-Bye Baby Pattern Update

Pattern No. 2007091

Please update PAGE 1 with the following corrections.

Cutting Guide For Travel Diaper Bag

From Fabric # 1, Cut:

2 {7-1/2" H x 7-1/2" W} Exterior Side Pockets-Lining

Cutting Guide For Batting/Interfacing

From Iron-on Interfacing, Cut:

2 {13" H x 15-1/2" W} Front/Back-Diaper Bag

2 {13" H x 8-1/2" W} Side Gussets

1 {8-1/2" H x 15-1/2" W} Bottom Gusset

2 {7-1/2" H x 14-1/2" W} Exterior Front/Back Pockets

2 {7-1/2" H x 7-1/2" W} Exterior Patch Pockets

4 {25" H x 3-1/2" W} Diaper Bag Handles

Please update PAGE 2 with the following corrections.

Making & Adding Exterior Pockets...See Diagrams C1 & C2

1. To make the Front Pockets for Diaper Bag Front, take two 7-1/2" squares and place them *right sides together*, matching all edges.
2. Pin then sew a seam along one 7-1/2" side. Press.

Making & Adding Exterior Pockets...See Diagrams C1 & C2

1. To make the Front Pockets for Diaper Bag Front, take two 7-1/2" squares and place them right sides together, matching all edges.
2. Pin then sew a seam along one 7-1/2" side. Press.
3. Pin rick rack on the 14-1/2" top-edge seam line of Pocket Front, then baste in place. Trim away excess rick rack.
4. With right sides together, stitch the Pocket and Pocket Lining together along the top edge. Turn right side out and press. Re-open the pocket and fuse a piece of 7-1/2" x 14-1/2" iron-on interfacing to the wrong side of Pocket Lining. Return the Pocket and Lining so they are facing wrong sides together and smooth out flat. Note: the Interfacing is now sandwiched between the Pocket & the Lining. Baste Sides and Bottom of Pocket together.
5. Repeat Steps 1-4 for remaining Back Pockets & Steps 3-4 for left & right Side Pockets, using 7-1/2" square Linings & Interfacings.
6. Pin Pocket Front to Diaper Bag Front, making sure the side and bottom edges match. Baste in place. Repeat this Step for Pocket and Diaper Bag Back. To divide Front/Back Pockets, straight stitch down center seam of Pockets. See Diagram C2 on next page.
7. Pin a Side Pocket to Side Gusset, making sure the side and bottom edges match. Baste in place. Repeat this Step for remaining Side Pocket & Side Gusset. See Diagram C2 on next page.

Please update PAGE 4 with the following corrections.

Adding Sashing...See Diagram F

1. *Delete Step 1* and continue with Steps 2-6 for adding the sashing.